






Größen. Modelle. Abmessungen. Antriebszuordnungstabellen

Torantriebszuordnung Schwingtore ohne / mit Deckenlaufschiene (N: Normstahl) / Andere Fabrikate (A) mit Deckenlaufschiene																										
	N	A	N	A	N	A	N	A	N	A	N	A	N	A	N	A	N	A	N	A	N	A	N	A	N	A
3000																										
2750																										
2500																										
2375																										
2250																										
2125																										
2000																										
Torbreite	2250	2375	2500	2750	3000	3250	3500	3750	4000	4250	4500	4750	5000													

Torantriebszuordnung für Seitensektionaltore													2 Flügelig												
3500																									
3250																									
3000																									
2750																									
2625																									
2500																									
2375																									
2250																									
2125																									
2000																									
Torbreite	2250	2375	2500	2750	3000	3250	3500	3750	4000	4500	5000	5500	6000	7000	8000	9000	10000	11000	12000						

g60 Antriebszuordnung Automatik-Tor														
3000														
2800														
2650														
2500														
2375														
2250														
2125														
2000														
1900														
Torbreite	2000	2250	2500	2750	3000	3250	3500	3750	4000	4250	4500	4750	5000	

Torantriebszuordnung Deckensektionaltore Euroserie und Alurahmen – Ausführung Normal- und Niedrigsturz																											
	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	EURO	ALU	
3125																											
3000																											
2875																											
2750																											
2625																											
2500																											
2375																											
2250																											
2125																											
2000																											
1875																											
Torbreite	2250	2375	2500	2750	3000	3250	3500	3750	4000	4250	4500	4750	5000														

-  Magic 600
Gesamtlänge: 3505 mm, Hubweg: 2890 mm
-  Magic 600 lang
Gesamtlänge: 4593 mm, Hubweg: 3978 mm
-  Magic 1000
Gesamtlänge: 3505 mm, Hubweg: 2890 mm
-  Magic 1000 NG 3
Gesamtlänge: 5681 mm, Hubweg: 5066 mm
-  Magic 1000 NG 4
Gesamtlänge: 7857 mm, Hubweg: 7242 mm